




SERIES KL18

- 7 Pin Tubular Key
- Max 1000 Key Codes



CHARACTERISTICS

- 7 Pin Tubular High Security Key
- 3 to 5 Indexing Positions
- 45°, 90°, Mixed 45° and 90° Detent Angles
- Single pole or Double pole Switching
- Max 1000 Key Codes

SPECIFICATIONS

- Contact Rating:** 4A @ 125 VAC or 28 VDC - 2A @ 250 VAC
- Contact Resistance:** <math>< 10 \text{ m } \Omega</math>
- Insulation Resistance:** 1000 Ω min.
- Dielectric Strength:** 1000 V RMS Min @ sea level
- Electric Life:** 6.000 make & break cycles @ full load

MATERIALS

- Lock Housing:** Zinc alloy Die-casted & Nickel plated
- Cylinder:** 5 Disk tumbler in Zinc alloy Die-casted & Nickel plated
- Keys:** Brass or Brass Nickel-plated
- Contacts:** Hard Copper alloy Silver plated
- Mounting Nut:** Zinc alloy Die-casted & Nickel plated

HOW TO ORDER



SERIES

CUT-OUT DIAMETER

P/N CONFIGURATOR

- Choose:
- Nr of Positions
 - Indexing
 - Nr of Poles
 - Layout
 - Terminal Connections
 - Key pull-out

OPTIONS

- (*) Same Key supplied standard
- (*) When ordering specify same Key or different Keys (max as specified in characteristics)
- (*) Each Key is identified with a Key Code
- (*) Min Qty per lot apply for different Keys - Please enquire -
- (*) Repeat orders can be supplied with specific Key Code (subject to min lot orders) - Please enquire -
- (*) Key Codes to fit other suppliers lock available on request - Please enquire -

